

➤ X- Y Axis Spray Coating Machines

1. Standalone X-Y Axis Spray Coating Machine



➤ **Product Parameters:**

Product Parameters	Standalone X-Y Axis Spray Coating Machine
Electrical Power Supply	415 VAC, 50 Hz
Pneumatic Air Supply	4-6 bar
Auto Spray Gun	Iwata Make 1.2 mm – 2 Nos
Spraying Area	400 mm / 600 mm / 800 mm / 1000 mm
MS Pressure Feed Tank with stirrer motor	9 lit / 20 lit / 40 lit - 1 Nos
Gun Cleaning Tank	2 lit – 1 Nos
Cubic Feet per Minute (CFM)	25

2. Conveyorized X-Y Axis Spray Coating Machine without Heater.



➤ Product Parameters:

Product Parameters	Conveyorized X-Y Axis Spray Coating Machine without Heater
Electrical Power Supply	415 VAC, 50 Hz
Pneumatic Air Supply	4-6 bar
Auto Spray Gun	Iwata Make 1.2 mm – 2 Nos
Spraying Area	400 mm / 600 mm / 800 mm / 1000 mm
MS Pressure Feed Tank with stirrer motor	9 lit /20 lit / 40 lit - 2 Nos
Gun Cleaning Tank	2 lit – 1 Nos
Cubic Feet per Minute (CFM)	25
Additional Item	Temperature Data Logger

3. Single Station ConveyORIZED X -Y Axis Spray Coating Machine with Two Heater.



➤ Product Parameters:

Product Parameters	Single Station ConveyORIZED X -Y Axis Spray Coating Machine with Two Heater
Electrical Power Supply	415 VA C, 50Hz
Pneumatic Air Supply	4-6 bar
Auto Spray Gun	Iwata Make 1.2 mm – 2 Nos
Heating Source	Electrical Heater Coil – 1 Nos
Spraying Area	400mm / 600mm / 800mm / 1000mm
MS Pressure Feed Tank with stirrer motor	9 lit / 20 lit / 40 lit -1 Nos
Gun Cleaning Tank	2 lit - 1 Nos
Cubic Feet per Minute (CFM)	25
Additional Items	Temperature Data Logger

4. Two Station Conveyorized X-Y Axis Spray Coating Machine with Three Heater.



➤ Product Parameters:

Product Parameters	Two Station Conveyorized X-Y Axis Spray Coating Machine with Three Heater
Electrical Power Supply	415 VAC, 50 Hz
Pneumatic Air Supply	4-6 bar
Spraying Stations	For Primer & Topcoat
Auto Spray Gun	Iwata Make 1.2 mm – 4 Nos
Heating Source	Electrical Heater Coil – 2 Nos
Spraying Area	400 mm / 600 mm / 800 mm / 1000 mm
MS Pressure Feed Tank with stirrer motor	9 lit /20 lit /40 lit -2 Nos
Gun Cleaning Tank	2 lit – 2 Nos
Cubic Feet per Minute (CFM)	44
Additional Items	Temperature Data Logger

5. Elliptical Conveyorized X-Y Axis Spray Machine.



➤ Product Parameters:

Product Parameters	Elliptical Conveyorized X-Y Axis Spray Machine
Electrical Power Supply	415 VAC, 50 Hz
Pneumatic Air Supply	4-6 bar
Spraying Station	For Primer & Topcoat – 2 Nos
Auto Spray Gun	Iwata Make 1.2 mm – 4 Nos
Heating Source	Electrical Heater Coil – 3 Nos
Spraying Area	400 mm, 600 mm, 800 mm & 1000 mm
MS Pressure Feed Tank with stirrer motor	9 lit / 20 lit / 40 lit - 2 Nos
Chemlok Container with Diaphragm Pump with electric stirrer	9 lit / 20 lit / 40 lit - 2 Nos
Gun Cleaning Tank	2 lit – 2 Nos
Cubic Feet per Minute (CFM)	44